

safety shoe Arctos B low,

The Arctos B safety shoe line offers a clear design for tough applications. Designed for the highest loads in extreme outdoor conditions: This line convinces with high-quality, particularly robust nubuck leather and a slip-resistant PU sole technology.

Article-No.: 140



Product details:	safety shoe Arctos B low, S3 - metal free, ESD
Colour:	schwarz
Size:	38,39,40,41,42,43,Groesse:44,45,46,47
Standardize:	DIN EN ISO 20345:2011 - S3
Packing Units:	Paar
Shoe shape:	Low cut
Protection level:	S3
Slip resistance:	SRC - Slip resistance on ceramic tile floors with NaLS and on steel floors with glycerine (SRA + SRB = SRC)
Toe Cap Model:	Composite toe cap
Midsole:	Penetration-resistant fabric midsole
Tongue:	Full, padded bellows textile tongue
Lining:	Fabric lining for natural ventilation
Outsole:	PU
Norms:	EN ISO 20345:2011 - Protection footwear for the commercial sector EN 61340-4-3:2001 - Protection for electrostatic discharge
Additional requirements for special applications:	A - Antistatic footwear (between 1.10 ⁵ Ohm and 1.10 ⁹ Ohm) CI - Thermal cold insulation of the sole (by temperature < 10°C) E - Heel area energy absorption (= 20 Joule) FO - Oil and petrol resistant sole (standard for EN ISO 20345:2011, EN ISO 20346:2011 and EN ISO 20347:2012) P - Pierce resistant midsole (= 1100 N.) WRU - Shoe upper, water penetration and water absorption (60min = water absorption < 30%)
Upper material:	Nubuck leather
Extras:	Heel-stabilizing system Metal-free equipment ESD-Equipment
Industry:	Construction / Waste / Recycling Service / Logistics / Facility management Craftsmanship / Manufacturing industry Heavy industry Agricultur / Garden Landscaping / Forest and wood management Light industry

