



protect ibex laced boot

laced boot Ibex S3, boot from cow grain leather, plastic cap and pierce-resistant fabric midsole, slip resistant 2-layer PU outsole, antistatic, oil- and acid-resistant sole, ankle, bootleg border and flap cushion, continuously and ergonomically formed inner sole, integrated upper cap

Article-No.: 2345

Product details:	protect ibex laced boot S3
Material:	leather
Colour:	black / grey
Size:	36,37,38,39,40,41,42,43,Groesse:44,45,46,47
Standardize:	DIN EN ISO 20345:2011 - S3
Packing Units:	10 Paar
Shoe shape:	Mid cut
Protection level:	S3
Slip resistance:	SRA - Slip resistant on ceramic tiles with sodium laurel sulphate lubricants
Toe Cap Model:	Composite toe cap
Midsole:	Penetration-resistant fabric midsole
Tongue:	Padded bellows leather tongue
Lining:	Fabric lining for natural ventilation
Outsole:	PU
Norms:	EN ISO 20345:2011 - Protection footwear for the commercial sector
Additional requirements for special applications:	A - Antistatic footwear (between $1 \cdot 10^5$ Ohm and $1 \cdot 10^9$ Ohm) E - Heel area energy absorption (= 20 Joule) FO - Oil and petrol resistant sole (standard for EN ISO 20345:2011, EN ISO 20346:2011 and EN ISO 20347:2012) P - Pierce resistant midsole (= 1100 N.) WRU - Shoe upper, water penetration and water absorption (60min = water absorption < 30%)
Upper material:	Cowhide leather
Extras:	Metal-free equipment Overcap
Industry:	Construction / Waste / Recycling Heavy industry Agricultur / Garden Landscaping / Forest and wood management Light industry