



safety shoe Arcots L low,

The safety shoe line Arcots L - dynamic design meets well thought-out means, excellent grip, very good fit, particularly comfortable

Article no.: 142

Coating description:	safety shoe Arcots L low, S3 - metal free, ESD
Size:	38, 39, 40, 41, 42, 43, 44, 45, 46, 47
Packaging units:	1 pair, 8 pair
Extras:	Metal-free equipment ESD-compliant equipment Leather-free equipment
Sector:	Services / logistics / facility management Craft / manufacturing industry Light industry Heavy industry Construction / Waste / Recycling
Shoe shape:	Low shoe
Protection class:	S3
Slip resistance:	SRC - Slip resistance on ceramic tile floors with NaLS and on steel floors with glycerine (SRA + SRB=SRC)
Protective toe cap:	Plastic cap
midsole:	Penetration-resistant fabric midsole
tongue:	Padded textile pocket
Liner:	Breathable textile lining
Outsole:	PU
Additional requirements for special applications:	A - Antistatic shoe (from 1.10 ^{^5} OHM- 1.10 ^{^9} OHM) FO - Oil and petrol resistant sole (standard in the EN ISO 20345:2011, EN ISO 20346:2011 and EN ISO 20347:2012 standards) E - Energy absorption in the heel area (= 20 joules) WRU - upper part of the shoe, water penetration and water absorption (60min = water absorption < 30%) P - puncture resistance (= 1100 N.)
Upper material:	microfibre